



New spearhead, its high-end construction combined with nano ceramic technology provides a deep black shade, allowing privacy while effectively rejecting heat.

## Certificeringer



**Garanti SOLAR SCREEN®**  
 Se Meddelelsen "Nye Garantier For De Eksterne Film"



**Brandsikkerhedsvurdering**



**Opbevaring Fra -5°C Til +40°C**  
 3 år



**Reach Rohs Kompatibel**  
 Respekteret



**Tilgængelige Bredder**  
 152cm

## Konstruktion

1. Hard scratch resistant layer, for durability and ease of maintenance during window cleaning
2. High optical quality dyed polyester without optical distortion
3. Bonding adhesive
4. High optical quality dyed polyester, with anti-heat nano ceramic particles
5. PS adhesive, glass polymerization within 15 days
6. Protection release liner, disposable after installation

## Vedligeholdelsesanvisninger

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

## Teknisk Datablad

|                                     |              |
|-------------------------------------|--------------|
| Ultraviolet Transmission            | 1%           |
| Transmission Af Synligt Lys         | 5%           |
| Refleksion Af Udendørs Synligt Lys  | 6%           |
| Refleksion Af Indendørs Synligt Lys | 5%           |
| Samlet Afvisning Af Solenergi       | 67%          |
| Solforhold :                        |              |
| Refleksion Af Solenergi             | 7%           |
| Absorption Af Solenergi             | 76%          |
| Transmission Af Solenergi           | 16%          |
| Reduktion Af Solblænding            | 94%          |
| Afvist Infrarød (760-2500 Nm)       | 85%          |
| Installationstype                   | Indvendig    |
| Rullelængde                         | 30.5 meter m |
| Filmkomposition                     | PET          |
| Tykkelse                            | 50µ          |
| Farve Fra Ydersiden                 | BLACK        |

## Installationsrådgivning

Vertikal Position Och För En Normal Glasyta\*

|                                  |   |
|----------------------------------|---|
| Klar Enkeltrude                  | ! |
| Tonet Enkeltrude                 | × |
| Reflekterende Tonet Enkeltrude   | ! |
| Klar Dobbelttrude                | × |
| Tonet Dobbelttrude               | × |
| Reflekterende Tonet Dobbelttrude | ! |
| Gasfyldt Dobbelttrude            | × |
| Stadip Ext. Klar Dobbelttrude    | × |
| Stadip Int. Klar Dobbelttrude    | × |

✓ Ja ✗ Ikke Anbefalet ! Advarsel

\*Recommendations provided on the basis of a glazed surface covering up to 2.5m², contact us for definitive details or to obtain a thermal shock analysis report.

Oplysningerne på denne informationsark er ikke bindende, SOLAR SCREEN® forbeholder sig retten til når som helst at ændre sammensætningen af deres produkter. Se vores garantibeviser og generelle salgsbetingelser.