



Mat Acid Grey privacy films are designed to provide protection against the scrutiny of prying eyes. Whilst completely opalescent, the film still allows most natural light to pass through. In addition, its slightly grey appearance will soothe the eye compared to a white film.

Certifications


Warranty SOLAR SCREEN®

5 years
 See the 'New guarantees for outdoor products' notice


Fire-Resistance Rating

M1


Storage From -5°C To +40°C

3 years


Reach Rohs Compliant

Respected


Widths Available

152cm

Construction

1. 75μ monomer PVC
2. Half Permanent Adhesive, allowing the "degassing" of the actual surface, and limits the adhesive transfer during removal
3. Paper release liner allowing digital cutting

Maintenance Instructions

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Technical Datasheet

Ultraviolet Transmission	>25%
Visible Light Transmission	60%
Reflection Of External Visible Light	18%
Reflection Of Internal Visible Light	18%
Total Solar Energy Rejected	28%
Total Solar Energy Rejected 2*	29%
Solar Ratio :	
Solar Energy Reflection	18%
Solar Energy Absorption	15%
Solar Energy Transmission	67%
Reduction In Solar Glare	40%
G-Value	0.71
U-Value	5.6
Installation Type	Interior
Roll Length	50 meters m
Film Composition	PVC
Thickness	75μ
Colour From The Outside	GREY

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	✓
Reflective Tinted Single Pane	✓
Clear Double Pane	✓
Tinted Double Pane	✓
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	✓
Stadip Ext. Clear Double Pane	✓
Stadip Int. Clear Double Pane	✓

✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m².

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.