



The Europa decorative film allows you to effectively customize your windows and glass partitions. It features a pattern composed of 44mm frosted bands arranged horizontally and separated by 10 mm clear aspect bands.

Certifications



Warranty SOLAR SCREEN®

5 years

See the 'New guarantees for outdoor products' notice



Fire-Resistance Rating

M1



Storage From -5°C To +40°C

3 years



Reach Rohs Compliant

Respected



Widths Available

152cm

Construction

1. High optical quality polyester with printed design
2. PS adhesive, glass polymerization within 15 days
3. Protection release liner, disposable after installation

Maintenance Instructions

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Technical Datasheet

Solar Ratio :

Solar Energy Reflection

Solar Energy Absorption

Solar Energy Transmission

Installation Type

Interior

Roll Length

30.5 meters m

Film Composition

PET

Thickness

40μ

Colour From The Outside

FROSTED

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane



Tinted Single Pane



Reflective Tinted Single Pane



Clear Double Pane



Tinted Double Pane



Reflective Tinted Double Pane



Gas-Filled Double Pane - Low E



Stadip Ext. Clear Double Pane



Stadip Int. Clear Double Pane



✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m².

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.