



Go on an adventure with the Scale decorative film! This film decorates your windows and glass partitions to create an absolutely authentic and wild atmosphere. The use of a discretion film is ideal to embellish your space while preserving your privacy.

Certifications



Warranty SOLAR SCREEN®
5 years
See the 'New guarantees for outdoor products' notice



Fire-Resistance Rating
M1



Storage From -5°C To +40°C
3 years



Reach Rohs Compliant
Respected



Widths Available
152cm

Construction

1. High optical quality polyester with printed design
2. PS adhesive, glass polymerization within 15 days
3. Protection release liner, disposable after installation

Maintenance Instructions

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Technical Datasheet

Visible Light Transmission	0%
Reflection Of External Visible Light	0%
Reflection Of Internal Visible Light	0%
Solar Ratio :	
Solar Energy Reflection	0%
Solar Energy Absorption	0%
Solar Energy Transmission	0%
Reduction In Solar Glare	0%
Installation Type	Interior
Roll Length	30.5 meters m
Film Composition	PET
Thickness	40μ
Colour From The Outside	FROSTED

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	✓
Reflective Tinted Single Pane	✓
Clear Double Pane	✓
Tinted Double Pane	✓
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	✓
Stadip Ext. Clear Double Pane	✓
Stadip Int. Clear Double Pane	✓

✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m².

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.