



The Structur decorative film allows you to effectively customize your windows and glass partitions. It is decorated with frosted bands of alternating width (35 mm and 5 mm), separated from each other by 5 mm clear aspect bands.

Certifications



Warranty SOLAR SCREEN®
5 years
See the 'New guarantees for outdoor products' notice



Fire-Resistance Rating
M1



Storage From -5°C To +40°C
3 years



Reach Rohs Compliant
Respected



Widths Available
152cm

Construction

1. High optical quality polyester with printed design
2. PS adhesive, glass polymerization within 15 days
3. Protection release liner, disposable after installation

Maintenance Instructions

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Technical Datasheet

Solar Ratio :

Solar Energy Reflection
Solar Energy Absorption
Solar Energy Transmission

Installation Type Interior

Roll Length 50 meters m

Film Composition PET

Thickness 40μ

Colour From The Outside FROSTED

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	✓
Reflective Tinted Single Pane	✓
Clear Double Pane	✓
Tinted Double Pane	✓
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	✓
Stadip Ext. Clear Double Pane	✓
Stadip Int. Clear Double Pane	✓

✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m².

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.