



Silver 80 XC films are highly effective at reducing solar heat gain, whilst at the same time continuing to allow some natural light transmission. This film provides a good level of protection against solar glare, whilst its one-way mirror aspect further guarantees privacy from prying eyes. Its modern design immediately lends a contemporary feel to any building exterior.

Certifications



Warranty SOLAR SCREEN®

7 years
 See the 'New guarantees for outdoor products' notice



Fire-Resistance Rating

M1



Storage From -5°C To +40°C

3 years



Reach Rohs Compliant

Respected



European Standard EN 12600

3b3



Widths Available

91cm 122cm 152cm 183cm

Construction

1. Hard scratch resistant layer, for durability and ease of maintenance during window cleaning
2. High optical quality polyester, with anti IR metal particles deposit
3. Bonding adhesive
4. High optical quality polyester
5. PS adhesive, glass polymerization within 15 days
6. Protection release liner, disposable after installation

Maintenance Instructions

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Technical Datasheet

Ultraviolet Transmission	1%
Visible Light Transmission	16%
Reflection Of External Visible Light	62%
Reflection Of Internal Visible Light	60%
Total Solar Energy Rejected	82%
Total Solar Energy Rejected 2*	87%
Solar Ratio :	
Solar Energy Reflection	67%
Solar Energy Absorption	20%
Solar Energy Transmission	13%
Reduction In Solar Glare	84%
G-Value	0.18
U-Value	5.1
Shading Coefficient	0.2
Installation Type	Exterior
Roll Length	30.5 meters m
Film Composition	PET
Thickness	60µ
Colour From The Outside	SILVER

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	✓
Reflective Tinted Single Pane	✓
Clear Double Pane	✓
Tinted Double Pane	✓
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	✓
Stadip Ext. Clear Double Pane	✓
Stadip Int. Clear Double Pane	✓

✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m², contact us for definitive details or to obtain a thermal chock analysis report.

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.