



Mat White privacy films are designed to provide protection against the scrutiny of prying eyes. Whilst completely opalescent, the film still allows most natural light to pass through.

Certifications


Warranty SOLAR SCREEN®

10 years
See the 'New guarantees for outdoor products' notice


Fire-Resistance Rating
 M1


Storage From -5°C To +40°C
3 years



Reach Rohs Compliant
Respected



Widths Available
92cm 122cm 152cm 183cm

Construction

1. Frosted polyester with satin surface
2. Bonding adhesive
3. High optical quality polyester
4. PS adhesive, glass polymerization within 15 days
5. Protection release liner, disposable after installation

Maintenance Instructions

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Technical Datasheet

Ultraviolet Transmission	5%
Visible Light Transmission	69%
Reflection Of External Visible Light	26%
Reflection Of Internal Visible Light	18%
Total Solar Energy Rejected	29%
Total Solar Energy Rejected 2*	29%
Solar Ratio :	
Solar Energy Reflection	18%
Solar Energy Absorption	19%
Solar Energy Transmission	63%
Reduction In Solar Glare	27%
G-Value	0.71
U-Value	5.6
Shading Coefficient	0.8
Installation Type	Interior
Roll Length	30.5 meters m
Film Composition	PET
Thickness	60μ
Colour From The Outside	SAND

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	✓
Reflective Tinted Single Pane	✓
Clear Double Pane	✓
Tinted Double Pane	✓
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	✓
Stadip Ext. Clear Double Pane	✓
Stadip Int. Clear Double Pane	✓

✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m².

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.