



Applied to clear glass, the transparent Raspberry C film bestows a red/pink tint to the glass without diminishing its transparent properties. It is the perfect way to enliven any interior glazing (such as partitions, shower screens, etc.) with a touch of colour.

Certifications



Warranty SOLAR SCREEN®
 5 years
 See the 'New guarantees for outdoor products' notice



Fire-Resistance Rating
 M1



Storage From -5°C To +40°C
 3 years



Reach Rohs Compliant
 Respected



Widths Available
 152cm

Construction

1. common scratch-resistant hard coat for durability and ease of maintenance when cleaning windows
2. High-quality polyester without optical distortion
3. PS adhesive, cures with glass within 15 days
4. adhesive protection liner, disposable after application

Maintenance Instructions

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Technical Datasheet

Ultraviolet Transmission	1%
Visible Light Transmission	22%
Reflection Of External Visible Light	10%
Reflection Of Internal Visible Light	10%
Total Solar Energy Rejected	36%
Total Solar Energy Rejected 2*	32%
Solar Ratio :	
Solar Energy Reflection	11%
Solar Energy Absorption	47%
Solar Energy Transmission	42%
Reduction In Solar Glare	80%
G-Value	0.69
U-Value	5.7
Installation Type	Interior
Roll Length	30.5 meters m
Film Composition	PET
Thickness	40µ
Colour From The Outside	RASPBERRY

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	!
Reflective Tinted Single Pane	✓
Clear Double Pane	!
Tinted Double Pane	!
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	!
Stadip Ext. Clear Double Pane	!
Stadip Int. Clear Double Pane	✗

✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m², contact us for definitive details or to obtain a thermal chock analysis report.

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.