



Applied to clear glass, the transparent Turquoise C film bestows a blue/green tint to the glass without diminishing its transparent properties. It is the perfect way to enliven any interior glazing (such as partitions, shower screens, etc.) with a touch of colour.

### Certifications


**Warranty SOLAR SCREEN®**

5 years  
See the 'New guarantees for outdoor products' notice


**Fire-Resistance Rating**

M1


**Storage From -5°C To +40°C**

3 years


**Reach Rohs Compliant**

Respected


**Widths Available**

152cm

### Construction

1. common scratch-resistant hard coat for durability and ease of maintenance when cleaning windows
2. High-quality polyester without optical distortion
3. PS adhesive, cures with glass within 15 days
4. adhesive protection liner, disposable after application

### Maintenance Instructions

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

### Technical Datasheet

|                                      |               |
|--------------------------------------|---------------|
| Ultraviolet Transmission             | 1%            |
| Visible Light Transmission           | 44%           |
| Reflection Of External Visible Light | 8%            |
| Reflection Of Internal Visible Light | 8%            |
| Total Solar Energy Rejected          | 29%           |
| Total Solar Energy Rejected 2*       | 26%           |
| Solar Ratio :                        |               |
| Solar Energy Reflection              | 9%            |
| Solar Energy Absorption              | 40%           |
| Solar Energy Transmission            | 51%           |
| Reduction In Solar Glare             | 50%           |
| G-Value                              | 0.69          |
| U-Value                              | 5.7           |
| Installation Type                    | Interior      |
| Roll Length                          | 30.5 meters m |
| Film Composition                     | PET           |
| Thickness                            | 40µ           |
| Colour From The Outside              | TURQUOISE     |

### Installation Advice

Vertical position and standard glass surface\*

|                                |   |
|--------------------------------|---|
| Clear Single Pane              | ✓ |
| Tinted Single Pane             | ! |
| Reflective Tinted Single Pane  | ✓ |
| Clear Double Pane              | ✓ |
| Tinted Double Pane             | ! |
| Reflective Tinted Double Pane  | ✓ |
| Gas-Filled Double Pane - Low E | ✓ |
| Stadip Ext. Clear Double Pane  | ✓ |
| Stadip Int. Clear Double Pane  | ! |

✓ Yes ✗ Not Recommended ! Caution

\*Recommendations provided on the basis of a glazed surface covering up to 2.5m², contact us for definitive details or to obtain a thermal chock analysis report.

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.