



Applied to clear glass, the transparent Blue Ocean C film bestows a blue tint to the glass without diminishing its transparent properties. It is the perfect way to enliven any interior glazing (such as partitions, shower screens, etc.) with a touch of colour.

Certifications


Warranty SOLAR SCREEN®

5 years
See the 'New guarantees for outdoor products' notice


Fire-Resistance Rating

M1


Storage From -5°C To +40°C

3 years


Reach Rohs Compliant

Respected


Widths Available

152cm

Construction

1. common scratch-resistant hard coat for durability and ease of maintenance when cleaning windows
2. High-quality polyester without optical distortion
3. PS adhesive, cures with glass within 15 days
4. adhesive protection liner, disposable after application

Maintenance Instructions

Soapy water solution (ref. sun pose 0808 or 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Technical Datasheet

Ultraviolet Transmission	1%
Visible Light Transmission	24%
Reflection Of External Visible Light	7%
Reflection Of Internal Visible Light	7%
Total Solar Energy Rejected	32%
Total Solar Energy Rejected 2*	29%
Solar Ratio :	
Solar Energy Reflection	9%
Solar Energy Absorption	47%
Solar Energy Transmission	44%
Reduction In Solar Glare	60%
G-Value	0.69
U-Value	5.7
Installation Type	Interior
Roll Length	30.5 meters m
Film Composition	PET
Thickness	40µ
Colour From The Outside	BLUE

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	!
Reflective Tinted Single Pane	✓
Clear Double Pane	!
Tinted Double Pane	!
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	!
Stadip Ext. Clear Double Pane	!
Stadip Int. Clear Double Pane	✗

✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m², contact us for definitive details or to obtain a thermal chock analysis report.

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.