



Clear 4 XC film secures your windows and prevents broken glass from scattering in the event of an impact. Perfectly transparent and easy to apply.

### Certifications



#### Warranty SOLAR SCREEN®

up to 5 years  
See the 'New guarantees for outdoor products' notice



#### Fire-Resistance Rating

M1



#### Storage From -5°C To +40°C

3 years



#### Reach Rohs Compliant

Respected



#### Widths Available

122cm 152cm 183cm

### Construction

1. Hard scratch resistant layer, for durability and ease of maintenance during window cleaning
2. High optical quality polyester
3. Reinforced PS adhesive to accompany the elasticity of the film in case of impact, glass polymerization within 30 days
4. Protection release liner, disposable after installation

### Maintenance Instructions

Safety film with reinforced PS adhesive requiring a suitable application solution (Film On ref 600-F0355 and 2cl/litre of water) and a suitable safety squeegee 150-054/150-055/150-056. Do not clean for at least 1 month and do not apply stickers or other adhesives to the film.

### Technical Datasheet

|                                      |               |
|--------------------------------------|---------------|
| Ultraviolet Transmission             | 1%            |
| Visible Light Transmission           | 91%           |
| Reflection Of External Visible Light | 8%            |
| Reflection Of Internal Visible Light | 8%            |
| Total Solar Energy Rejected          | 17%           |
| Total Solar Energy Rejected 2*       | 18%           |
| Solar Ratio :                        |               |
| Solar Energy Reflection              | 10%           |
| Solar Energy Absorption              | 8%            |
| Solar Energy Transmission            | 82%           |
| Reduction In Solar Glare             | 8%            |
| G-Value                              | 0.83          |
| U-Value                              | 5.7           |
| Shading Coefficient                  | 0.9           |
| Installation Type                    | Exterior      |
| Roll Length                          | 30.5 meters m |
| Film Composition                     | PET           |
| Thickness                            | 120μ          |
| Colour From The Outside              | TRANSPARENT   |

### Installation Advice

Vertical position and standard glass surface\*

|                                |   |
|--------------------------------|---|
| Clear Single Pane              | ✓ |
| Tinted Single Pane             | ✓ |
| Reflective Tinted Single Pane  | ✓ |
| Clear Double Pane              | ✓ |
| Tinted Double Pane             | ✓ |
| Reflective Tinted Double Pane  | ✓ |
| Gas-Filled Double Pane - Low E | ✓ |
| Stadip Ext. Clear Double Pane  | ✓ |
| Stadip Int. Clear Double Pane  | ✓ |

✓ Yes ✗ Not Recommended ! Caution

\*Recommendations provided on the basis of a glazed surface covering up to 2.5m².

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.