



This film laminated to a ferrous film transforms your smooth or glazed surfaces into an erasable whiteboard with the possibility of being able to set any documents using magnets.

Certifications



Warranty SOLAR SCREEN®
2 years
See the 'New guarantees for outdoor products' notice



Fire-Resistance Rating



Storage From -5°C To +40°C
3 years



Reach RoHS Compliant
Respected



Widths Available
120cm

Construction

1. White PVC compatible with erasable pen
2. Bonding adhesive
3. 500µ ferrous film
4. PS adhesive, polymerizes with glass within 15 days
5. Protection release liner, disposable after installation

Maintenance Instructions

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Technical Datasheet

Ultraviolet Transmission	1%
Reflection Of External Visible Light	80%
Reflection Of Internal Visible Light	5%
Total Solar Energy Rejected	99%
Total Solar Energy Rejected 2*	99%
Solar Ratio :	
Solar Energy Reflection	85%
Solar Energy Absorption	15%
Solar Energy Transmission	
Reduction In Solar Glare	100%
G-Value	0.05
U-Value	5
Installation Type	Interior
Roll Length	20 meters m
Film Composition	PET + IRON
Thickness	600µ
Colour From The Outside	WHITE

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane	!
Tinted Single Pane	!
Reflective Tinted Single Pane	!
Clear Double Pane	!
Tinted Double Pane	!
Reflective Tinted Double Pane	!
Gas-Filled Double Pane - Low E	!
Stadip Ext. Clear Double Pane	!
Stadip Int. Clear Double Pane	!

✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m², contact us for definitive details or to obtain a thermal chock analysis report.

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.