



This multi-layer film has many lives! Indeed, thanks to its 4 layers of 100 microns, it will protect your surfaces from graffiti and tags. Once the film is too visually damaged, you can simply remove the layer. You have 4 layers before you have to install a new film. In addition, this film will also reinforce your windows against accidents, aggression and explosion risks.

Certifications



Warranty SOLAR SCREEN®

5 years
See the 'New guarantees for outdoor products' notice



Fire-Resistance Rating



Storage From -5°C To +40°C
3 years



Reach Rohs Compliant
Respected



Widths Available
152cm

Construction

1. Hard scratch resistant layer, for durability and ease of maintenance during window cleaning
2. 100µ high optical quality polyester
3. Non permanent PS adhesive
4. Hard scratch resistant layer, for durability and ease of maintenance during window cleaning
5. 100µ high optical quality polyester
6. Non permanent PS adhesive
7. Hard scratch resistant layer, for durability and ease of maintenance during window cleaning
8. 100µ high optical quality polyester
9. Non permanent PS adhesive
10. Hard scratch resistant layer, for durability and ease of maintenance during window cleaning
11. 100µ high optical quality polyester
12. Non permanent PS adhesive
13. Protection release liner, disposable after installation

Maintenance Instructions

Safety film with reinforced PS adhesive requiring a suitable application solution (Film On ref 600-F0355 and 2cl/litre of water) and a suitable safety squeegee 150-054/150-055/150-056. Do not clean for at least 1 month and do not apply stickers or other adhesives to the film.

Technical Datasheet

Ultraviolet Transmission	2%
Visible Light Transmission	82%
Reflection Of External Visible Light	11%
Reflection Of Internal Visible Light	11%
Total Solar Energy Rejected	19%
Total Solar Energy Rejected 2*	19%
Solar Ratio :	
Solar Energy Reflection	9%
Solar Energy Absorption	14%
Solar Energy Transmission	77%
Reduction In Solar Glare	17%
G-Value	0.83
U-Value	5.7
Shading Coefficient	0.9
Installation Type	Interior
Roll Length	30.5 meters m
Film Composition	PET
Thickness	485µ
Colour From The Outside	TRANSPARENT

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	✓
Reflective Tinted Single Pane	✓
Clear Double Pane	✓
Tinted Double Pane	✓
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	✓
Stadip Ext. Clear Double Pane	✓
Stadip Int. Clear Double Pane	✓

✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m².

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.

