



Mat Light privacy films are designed to provide protection against the scrutiny of prying eyes. Whilst completely opalescent, the film still allows most natural light to pass through.

Certifications



Warranty SOLAR SCREEN®

10 years
See the 'New guarantees for outdoor products' notice



Fire-Resistance Rating

M1



Storage From -5°C To +40°C

3 years



Reach Rohs Compliant

Respected



Widths Available

152cm

Construction

1. Frosted polyester with satin surface
2. Bonding adhesive
3. High optical quality polyester
4. PS adhesive, glass polymerization within 15 days
5. Protection release liner, disposable after installation

Maintenance Instructions

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Technical Datasheet

Ultraviolet Transmission	5%
Visible Light Transmission	78%
Reflection Of External Visible Light	11%
Reflection Of Internal Visible Light	10%
Total Solar Energy Rejected	17%
Total Solar Energy Rejected 2*	15%
Solar Ratio :	
Solar Energy Reflection	10%
Solar Energy Absorption	10%
Solar Energy Transmission	78%
Reduction In Solar Glare	23%
G-Value	0.71
U-Value	5.6
Shading Coefficient	0.8
Installation Type	Interior
Roll Length	30.5 meters m
Film Composition	PET
Thickness	60μ
Colour From The Outside	SAND

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	✓
Reflective Tinted Single Pane	✓
Clear Double Pane	✓
Tinted Double Pane	✓
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	✓
Stadip Ext. Clear Double Pane	✓
Stadip Int. Clear Double Pane	✓

✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m².

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.