

The frosted effect as we like it, generous to the eye and touch. It brings a distinctive design while providing excellent privacy protection.

Certifications



Warranty SOLAR SCREEN®

5 ans
 See the 'New guarantees for outdoor products' notice



Fire-Resistance Rating M1



Storage From -5°C To +40°C 3 ans



Reach Rohs Compliant Respected



Widths Available 76cm 152cm

Construction

1. Dyed polyester without optical distortion
2. Bonding adhesive
3. High optical quality polyester, with anti IR metal particles deposit
4. PS adhesive, glass polymerization within 15 days
5. Protection release liner, disposable after installation

Maintenance Instructions

Soap-based water solution (ref. Film On 600-F0355), do not clean before at least 1 month, and do not apply stickers or other adhesive on the film.

Technical Datasheet

Ultraviolet Transmission	15%
Visible Light Transmission	75%
Reflection Of External Visible Light	0%
Reflection Of Internal Visible Light	0%
Total Solar Energy Rejected	0%
Total Solar Energy Rejected 2*	0%
Solar Ratio :	
Solar Energy Reflection	0%
Solar Energy Absorption	0%
Solar Energy Transmission	0%
Reduction In Solar Glare	0%
G-Value	0
U-Value	0
Heat Loss Reduction (Winter)	0
Rejected Infrared (760-2500 Nm)	0
Shading Coefficient	
Installation Type	Interior
Roll Length	30.5m m
Film Composition	PET
Thickness	239μ
Colour From The Outside	FROSTED

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	✓
Reflective Tinted Single Pane	✓
Clear Double Pane	✓
Tinted Double Pane	✓
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	✓
Stadip Ext. Clear Double Pane	✓
Stadip Int. Clear Double Pane	✓

✓ Yes ✗ Not Recommended ! Caution

*Advice based on glass surface area up to 2.5m².

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.